

You want to learn more about us?

Feel free to ask for a meeting on our premises.
Detailed information on the company and on
our product range is also available on-line at
www.huerner.de



HÜRNER

S C H W E I S S T E C H N I K

HÜRNER Schweißtechnik GmbH

Technologie Straße
35325 Mücke
GERMANY

Ph +49 6401 9127 0

E-Mail: op@huerner.de
Internet: www.huerner.de

10.2025



Your partner for HÜRNER Schweißtechnik:

KVG
Kunststoff-Vertriebs KG

KVG Kunststoff-Vertriebs KG

Feincheswiese 5
56424 Staudt
GERMANY

Ph +49 2602 68050

E-Mail: info@kvg-staudt.de
Internet: www.kvg-staudt.de

CNC ECO 2.0 500-630

EN

HÜRNER WhiteLine
CNC ECO 2.0

KVG
Kunststoff-Vertriebs KG

HÜRNER
S C H W E I S S T E C H N I K



Example picture

Stand-alone in Butt-Welding

Technical Specs	160 mm	200 mm	250 mm	315 mm	355 mm	500 mm	630 mm	800 mm	1000 mm	1200 mm
P/N 200-701-...	-162	-200	-250	-315	-355	-500	-630	-800	-100	-120
Welding range, O.D. (mm)	40–160	63–200	75–250	90–315	90–355	200–500	315–630	500–800	630–1000	630–1200
Power Supply	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz	400 V 50Hz,3P	400 V 50Hz,3P	400 V 50Hz,3P	400 V 50Hz,3P	400 V 50Hz,3P
Rated power (kW)	2.85	3.65	3.85	4.85	5.60	6.95	11.65	18.2	23.61	21.2
Overall weight with all components (kg)	80	91	125	179	216	372	581	1233	1397	1775
Reducer inserts	40, 50, 63, 75, 90, 110, 90, 110, 125, 140, 125, 140, 160, 180, 160, 180, 200, 225	63, 75, 90, 110, 90, 110, 125, 140, 125, 140, 160, 180, 160, 180, 200, 225	(63)*, 75, 90, 110, 90, 110, 125, 140, 125, 140, 160, 180, 160, 180, 200, 225	75, 90, 110, 125, 140, 160, 180, 200, 225	90, 110, 125, 140, 160, 180, 200, 225	90, 110, 125, 140, 160, 180, 200, 225	200, 225, 250, 280, 315, 355, 400, 450	315, 355, 400, 450, 500, 560, 630, 710	500, 560, 630, 710, 800, 900	630, 710, 800, 900, 1000
Welding neck support*)	■	■	■	■	■	■	■	■	■	■
Automatic, "jumping" heating element*)	■	–	■	■	■	■	■	–	–	–
Included standard delivery:										
CNC ECO hydraulic controller	■	■	■	■	■	■	■	■	■	■
Basic machine chassis	■	■	■	■	■	■	■	■	■	■
Facing tool with micro-switch	■	■	■	■	■	■	■	■	■	■
PTFE-coated heating element	■	■	■	■	■	■	■	■	■	■
Carrying rack	■	■	■	■	■	■	■	■	■	■
HÜRNER transport box for reducers and machine optional	■	■	■	■	–	–	–	–	–	–
HÜRNER aluminium reducers*)	■*)	–	■	■	■	■	■	■	■	■
HÜRNER steel reducers*)	■	■	–	–	–	–	–	–	–	–

*) Modified design: Screw-Fastened

*) Available as an option

The HÜRNER CNC ECO 2.0 is a high-quality and durable, next-generation CN-controlled plastic pipe butt-welding machine that has been developed in compliance, as applicable, with the machinery directive 2006/42/EC as amended. The design of the machine is such that with 12 basic machine chassis models, pipes from O.D. 40 through 1200 mm can be jointed.

The welding machines ship with a fully encased CNC hydraulic and control box of ingress protection IP 54 managing pressures up to 220 bar. Both the anti-stick-coated heating element and the facing tool are hooked up along with the machine chassis on the hydraulic and control box. No additional power distribution is needed.

Furthermore, all HÜRNER CNC ECO machines of the next generation allow an optional upgrade with a hardware-based input


voltage monitor, inclusive of the associated voltage recording capabilities.

Of course, the tried and tested input device, handheld scanner, continue to be available as options. All HÜRNER CNC ECO machines also feature a USB interface port and Bluetooth connectivity for download of the welding data to a USB stick as a short abstract or an extended report in the PDF format or for archiving them in the HÜRNER DataWork format.

Add to all the above the new HÜRNER WeldTrace app's QR code scanning capability, and comprehensive end-to-end tracing of all project and welding information is a given even years after the fact.

In their CNC ECO + 2.0 model version, all machines additionally feature the HDC – HÜRNER Distance Control – sensing system for accurate verification of proper welding and welding process preparation.

All components are covered by the HÜRNER warranty.



Industry version



Movement Pushbutton



Tag printer and label tags



Front panel

HÜRNER CNC ECO 2.0 characteristics

Automatic data logging	10,000 reports
Data input	RFID transponder, manually, bar code scanner ²⁾
System self-monitoring	Hardware-base input voltage monitor ²⁾ incl. data recording, system check, computerized maintenance management, including recording
Welding monitoring system	Welding pressures, welding times, ambient temperature, input voltage, memory control, motor operating temperature, heating element temperature, service schedule management, welding road/length
Traceability	Commission number 32 alphanumeric characters, RFID-fed ISO welder ID code, additional data 20 and 15 alphanumeric characters, ISO pipe codes, fitting data, pipe length, weather conditions, installing company, joint number, inventory number, display of maintaining company
Welding standard	DVS, WIS, SEDIGAS, UNI, UNI, NEN, and others upon request
Data output	USB A port for data transfer as short abstract or extended report in the PDF format to a USB stick or a label tag printer, incl. tag printer menu; transfer also possible in the HÜRNER DataWork format, CNC ECO 2.0 now with powerful download menu with date range selection, commission number selection, and download of all reports in memory
Languages	DE, EN, FR, BG, CS, ZH, NL, FI, GR, IT, NO, RO, SK, TR, RU, and others upon request
Display elements	Robust, high-resolution and temperature range-extended display screen with font size 8 mm, welding diagram with LED indicators
Miscellaneous	Keyboard switching, menu-controlled report review incl. search capability, ViewWeld feature, interactive carriage mover pushbutton on machine chassis, special memory backup feature
Standards, approvals, quality	Machinery directive 2006/42/EC (as applicable), DVS 2207, WEEE Reg. No. DE74849106, ISO 9001:2015, RoHS-compliant
Manufacturer warranty	12 months

*) optional

*) Retrofit kit for converting existing systems to industry version available upon request!